
Product name	: Carat Gold	Carat Silver
Article number	: 08037	08036
Supplier / Producer	: MOTIP DUPLI B.V.	
	Wolframweg 2	
	NL-8471 XC WOLVEGA	
	Telephone number	+31 561 – 69 44 00
	Telefax number	+31 561 – 69 44 31

Product description

High quality decorative lacquer to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic.

Product characteristics

Fast drying
Rub resistant
Metallic gloss
Non-fading and UV resistant
Resistant to weather influences
Scratch free and wear-resistant
Excellent adhesion



Physical and Chemical Characteristics

Contents	: 400 ml
Base	: Acrylic resin
VOC-content	: Approximately 93% w/w
Solid content	: Approximately 7% w/w
Coverage	: 1,25 to 1,75 m ²
Dust dry	: After approximately 5 minutes
Tack free	: After approximately 10 minutes
Hardened/re-sprayable	: After 1 hour
Heat resistant	: To 110°C

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust, sand the surface and apply a layer of Carat primer. When treating surfaces of plastic, first apply a layer of Carat plastic primer before applying the Carat primer. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.