

Product name	:	Carat Clear Lacquer		
Gloss	:	High Gloss	Satin Matt	Matt
Article number	:	08102	08103	08104
Supplier / Producer	:	MOTIP DUPLI B.V.		
		Wolfraamweg 2		
		NL-8471 XC WOLVEGA		
		Telephone number	+31 561 – 69 44 00	
		Telefax number	+31 561 – 69 44 31	

Product description

High quality clear lacquer for decoration purposes. To treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone, and various types of plastic.

Product characteristics

- Fast drying
- Excellent filling property
- Lasting gloss
- Scratch free and shock proof
- Resistant to weather influences
- Corrosion preventive
- UV-resistant and non-fading
- Excellent adhesion

Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Acrylic resin
Colour	:	Transparent
VOC-content	:	Approximately 91% w/w
Solid content	:	Approximately 9% w/w
Gloss	:	High gloss 90 at an angle of 60° Satin Matt 30 at an angle of 60° Matt 10 at an angle of 60°
Coverage	:	1,25 to 1,75 m ² / l
Dust dry	:	After approximately 5 minutes
Tack free	:	After approximately 10 minutes
Hardened/re-sprayable	:	After 1 hour
Heat resistant	:	To 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600).

Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the clear lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.